

ULTRALIGHT RINGS - 34MM MEDIUM 1.0" 4 SCREW ULTRALIGHT RINGS

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Designed to fit Mil-Std. 1913 scope bases, Nightforce rings are precisely manufactured to match the machined recess of a Nightforce Mil-Std. 1913 base, providing perfect alignment and accuracy. Nightforce rings are designed and produced in-house to exacting specifications entirely out of steel or from 7075-T6 aluminum with beta series titanium crossbolts and jaws. All Nightforce rings are 100% micro-radiused and honed in pairs for perfect fit of 30mm scope tubes to prevent the possibility of the rings damaging your scope.



Attributes

- Name: [34MM MEDIUM 1.0" 4 SCREW ULTRALIGHT RINGS](#)
- Manufacturer: [NIGHTFORCE](#)
- Product no.: 100012595
- Mfr. No.: A223
- Finish: Black
- Height: Medium
- Material: -
- Scope Tube Diameter: 34mm
- Size: Medium
- Style: Picatinny Rings
- Delivery weight: 0.023kg
- Shipping height: 20mm
- Shipping width: 140mm
- Shipping length: 155mm
- UPC: 847362005324

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [ULTRALIGHT RINGS 34MM MEDIUM 1.0" 4 SCREW ULTRALIGHT RINGS Safety Instruction Guide](#)
- [About Us](#)

ULTRALIGHT RINGS 34MM MEDIUM 1.0" 4 SCREW

ULTRALIGHT RINGS Safety Instruction Guide

Introduction

Thank you for purchasing the ULTRALIGHT RINGS 34MM MEDIUM 1.0" 4 SCREW ULTRALIGHT RINGS. This guide provides important safety information and instructions to ensure proper use and maintenance of the product. Please read this guide carefully before using the rings.

General Safety Guidelines

- Ensure the product is used only for its intended purpose as specified in this guide.
- Always check for damage or wear before installation and use. Do not use damaged products.
- Keep the product out of reach of children and vulnerable individuals.
- If you experience any issues or concerns with the product, discontinue use immediately and seek assistance.

Specific Safety Precautions for Use

- **Installation Safety:** Ensure that the rings are securely attached to the scope base to prevent accidents during use.
- **Weight Limitations:** Be aware of the weight limitations of your scope and ensure that the ULTRALIGHT RINGS can adequately support it.
- **Environmental Conditions:** Avoid using the rings in extreme weather conditions that may affect their performance or integrity.
- **Cleaning and Maintenance:** Use only recommended cleaning materials. Avoid solvents that could damage the rings.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench and appropriate screwdrivers.
- Ensure the scope and rifle are clean and free from debris.

2. Installation:

- Align the ULTRALIGHT RINGS with the MilStd. 1913 scope base.
- Securely attach the rings using the provided screws. Ensure that each screw is tightened to the manufacturer's specifications.
- Check for proper alignment of the scope tube within the rings.

3. Usage:

- After installation, inspect the rings and scope for any movement before each use.
- Regularly check the screws for tightness during use, especially after heavy recoil.
- Always handle the scope with care to avoid impacts that could misalign the rings.

Disposal Instructions

- Dispose of the ULTRALIGHT RINGS in accordance with local regulations.
- If the product is no longer usable, consider recycling materials where possible.
- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For any safety inquiries or concerns regarding the ULTRALIGHT RINGS, please contact the manufacturer or your retailer. Ensure that you have the product details available for reference.

By following these safety instructions, you can ensure a safe and effective experience with your ULTRALIGHT RINGS. Thank you for choosing our product, and enjoy your shooting experience!

About Us

Brownells Norge

Brownells Norge - Komplette utvalg av ladeutstyr, våpendeler, kuler, hylser, kikkerter, optikk og luftvåpen

Heiveien 882
4985 Vegårshei

www.brownells.no