

XRT X-RINGS PICATINNY SCOPE RINGS - TPS PRODUCTS XRT ALUMINUM RINGS 30MM X-HIGH

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

XRT Series X-Rings, bringing a whole new level of beauty and precision into an extremely rugged Picatinny platform scope mount. The X-Rings have been built from the bottom up to provide the extreme precision and accuracy that TPS rings have been known for over the last two decades. The ring bases begin from a solid billet of 7075-T6 aluminum and then machined with our unique Double-Lug Picatinny recoil shoulders from the solid billet. We have designed and engineered the Double-Lug recoil system to allow the parallelism and perpendicularity of the lugs to the ring bore to be within .0002, thereby providing repeatability that no other mount in the world with similar integrated lugs has done before. The X-Rings are specifically designed for the Mil-STD 1913 rail system. Because of the Double-Lug system, they do require two (2) accompanied cross-slots in a 1913 cross-slot configuration. The ring caps are secured with Four (4) 8-32 x 1/2" Camcar-Textron Torx drive screws and with the same unique design that allows you to tighten the left side of the cap, then the right side without the scope rotating. The edges and corners are fully radiused, preventing snagging, and providing a beautiful appearance to your rifle. The rings are securely attached to your rail with an oversized clamp system using Two (2) 8-32 x 1/2" Camcar-Textron Torx screws, preventing any chance your rings will loosen or move once installed. With unparalleled precision and holding force, and sleek design, these will meet the extreme expectations of any class shooter. SPECS: 7075-T651 Aluminum Alloy, matte black, hard anodized to Mil-A-8625 standards. .700" (17.8mm) wide. Height measured from the top of base to center of the ring. 30mm - High: .1.075" (31.11mm).



Attributes

- Name: [TPS PRODUCTS XRT ALUMINUM RINGS 30MM X-HIGH](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100036964
- Mfr. No.: 50583
- Finish: Matte Blue
- Height: 1.4"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: Extra High
- Style: Tactical Rings
- Delivery weight: 0.181kg
- Shipping height: 64mm
- Shipping width: 64mm
- Shipping length: 127mm
- UPC: 071611505833

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [XRT XRINGS PICATINNY SCOPE RINGS Safety Instruction Guide](#)
- [About Us](#)

XRT XRINGS PICATINNY SCOPE RINGS Safety Instruction Guide

Introduction

Thank you for choosing the XRT XRINGS Picatinny Scope Rings by TPS Products. This guide provides essential safety instructions and information to ensure the safe and effective use of your scope rings. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the scope rings are compatible with your scope and rifle.
- Always inspect the product for any damage or defects before use.
- Keep the scope rings out of reach of children and individuals who may not understand their use.
- Follow all local laws and regulations regarding firearm accessories and usage.
- Report any unsafe product experiences or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- **Installation Safety:**
 - Use proper tools when installing the scope rings to prevent injury or damage.
 - Ensure that the scope is securely mounted to avoid any movement during use.
- **Usage Safety:**
 - Always check that the scope rings are tightened correctly before using the firearm.
 - Avoid using excessive force when tightening screws to prevent stripping or breaking.
 - Do not use the scope rings if they show signs of wear or damage.
- **Environmental Safety:**
 - Store the scope rings in a dry, cool place to prevent corrosion and degradation.
 - Avoid exposing the scope rings to extreme temperatures or moisture.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a Torx screwdriver.
- Ensure the rifle is unloaded and safe to handle.

2. Installation:

- Align the scope rings with the Picatinny rail on your rifle.
- Insert the provided Torx screws into the crossslots of the rail.
- Tighten the screws gradually, alternating between the left and right sides to maintain even pressure.
- Ensure the scope is level and properly aligned before final tightening.

3. Adjustment:

- Once installed, adjust the scope to your desired position.

- Securely tighten the ring caps using the provided screws, ensuring no rotation of the scope occurs during tightening.

4. Final Check:

- After installation, doublecheck all screws and connections to ensure they are secure.
- Test the stability of the scope rings by gently shaking the scope to confirm no movement.

Disposal Instructions

- Dispose of packaging materials responsibly, following local recycling guidelines.
- If the scope rings are no longer usable, dispose of them in accordance with local waste disposal regulations.
- Do not throw away electronic components in regular trash; follow ewaste disposal guidelines if applicable.

Contact Information for Further Support

For any inquiries or further assistance regarding the XRT XRINGS Picatinny Scope Rings, please contact your local retailer or the manufacturer directly. Ensure you have your product information ready for a more efficient response.

By following these safety instructions, you can ensure a safe and enjoyable experience with your XRT XRINGS Picatinny Scope Rings. Thank you for your attention to safety and responsible usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk