

AR-15 BRAVO TRIGGERGUARDS - B5 SYSTEMS AR-15 TRIGGER GUARD ALUMINUM FDE

[Rifle Parts](#) > [Triggers Parts](#) > [Trigger Guards](#)

The B5 Systems Bravo trigger guard offers a drop in upgrade over the standard AR trigger guard. The enlarged profile allows for glove use in cold weather or tactical operation. The trigger guard also maintains the original swing down function for use with heavier winter gloves. Proudly made in the USA. FEATURES Made of 6061 aluminum or composite Mil-Spec Type III anodized finish. SPECS Weight: 3.00 oz. Length: 2.10 in. Height: 0.53 in.



Attributes

- Name: [B5 SYSTEMS AR-15 TRIGGER GUARD ALUMINUM FDE](#)
- Manufacturer: [B5 SYSTEMS](#)
- Product no.: 430104482
- Mfr. No.: ATG1103
- Finish: Flat Dark Earth
- Weapon type: AR-15
- Delivery weight: 0.227kg
- Shipping height: 13mm
- Shipping width: 102mm
- Shipping length: 152mm
- UPC: 814927020382

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [AR15 Bravo Trigger Guard Safety Instructions](#)
- [About Us](#)

AR15 Bravo Trigger Guard Safety Instructions

Introduction

Thank you for purchasing the B5 Systems AR15 Bravo Trigger Guard. This product is designed to enhance your AR15 firearm experience by providing a durable and functional upgrade to the standard trigger guard. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always handle firearms with care and ensure they are unloaded when installing or modifying components.
- Keep the trigger guard and surrounding areas clean and free from debris to prevent accidental discharge.
- Ensure that the trigger guard is installed correctly to prevent any potential hazards during use.
- Be aware of your surroundings and ensure that you are in a safe environment when using your firearm.

Specific Safety Precautions for Use

- Use gloves when handling the firearm in cold weather or tactical situations to maintain grip and control.
- Do not modify the trigger guard beyond its intended use as specified by the manufacturer.
- If you notice any wear, damage, or malfunction of the trigger guard, discontinue use immediately and consult a professional.
- Ensure that the trigger guard maintains its swingdown function, especially when using heavier gloves.

Instructions for Installation and Usage

1. Installation

- Ensure your firearm is unloaded and pointed in a safe direction.
- Remove the existing trigger guard by unscrewing it from the lower receiver.
- Align the B5 Systems Bravo Trigger Guard with the mounting holes on the lower receiver.
- Securely fasten the trigger guard using the provided screws, ensuring it is tightly in place but not overtightened.
- Check the swingdown function to confirm proper installation.

2. Usage

- When using the firearm, ensure that your fingers are off the trigger until ready to shoot.
- If wearing gloves, ensure they fit properly to maintain dexterity and control of the firearm.
- Regularly inspect the trigger guard for any signs of damage or wear, especially after extensive use.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste management regulations.
- If the trigger guard becomes damaged beyond repair, dispose of it in a manner that prevents any potential harm to the environment or public safety.

Contact Information for Further Support

For additional information or assistance regarding the B5 Systems AR15 Bravo Trigger Guard, please refer to the manufacturer's website or contact their customer support.

Conclusion

Following these safety instructions will help ensure your safe and enjoyable experience with the B5 Systems AR15 Bravo Trigger Guard. Always prioritize safety and adhere to local laws and regulations when using your firearm. Thank you for choosing B5 Systems.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk