

TOP RING BUBBLE LEVEL 6 SCREW - 34MM 6-SCREW TOP RING BUBBLE LEVEL

[Optics & Mounting](#) > [Optic Accessories](#) > [Scope Anti-Cant Devices](#)

The Nightforce Ring Cap Bubble Levels replace the top half of the ring of the Nightforce UniMount, Direct Mount and standard rings. Available with an integral ADI mount (ADI sold separately) or as a top half of ring and bubble level only.



Attributes

- Name: [34MM 6-SCREW TOP RING BUBBLE LEVEL](#)
- Manufacturer: [NIGHTFORCE](#)
- Product no.: 749013836
- Mfr. No.: A272
- Finish: Black
- Tube Size: 34mm
- Delivery weight: 0.045kg
- Shipping height: 30mm
- Shipping width: 117mm
- Shipping length: 137mm
- UPC: 847362006970

Item details

Made in USA

Table of Contents

- Startpage
- TOP RING BUBBLE LEVEL Safety Instruction Guide
- About Us

TOP RING BUBBLE LEVEL Safety Instruction Guide

Introduction

Thank you for choosing the TOP RING BUBBLE LEVEL. This product is designed to assist in achieving precise leveling for your scopes, ensuring enhanced accuracy during use. To ensure your safety and the proper functioning of this device, please read and follow these safety instructions carefully.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Always inspect the bubble level before use for any signs of damage.
- Avoid using the product if it is damaged or shows signs of wear.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform regularly.

Specific Safety Precautions for Use

- Do not exceed the recommended tube size of 34mm when using the bubble level.
- Ensure that the bubble level is securely attached to the scope before use.
- Avoid using the bubble level in extreme weather conditions, such as heavy rain or strong winds.
- Do not attempt to modify or repair the product yourself; contact a qualified professional for assistance.
- Always use the bubble level in a welllit environment to ensure visibility of the bubble.

Instructions for Installation and Usage

1. Installation:

- Remove the top half of your Nightforce UniMount, Direct Mount, or standard rings.
- Align the TOP RING BUBBLE LEVEL with the mounting area.
- Securely attach the bubble level to the scope ring, ensuring it fits snugly.
- If using an integral ADI mount, ensure it is installed according to the manufacturer's instructions.

2. Usage:

- Position your scope on a stable surface.
- Look through the scope to check the bubble level; ensure the bubble is centered within the level.
- Adjust the scope as necessary until the bubble is properly centered.
- Once aligned, securely tighten all mounting screws to prevent movement during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste.
- Do not dispose of the product in household waste.
- If you are unsure about disposal methods, contact your local waste management authority for guidance.

Contact Information for Further Support

For any questions or concerns regarding the TOP RING BUBBLE LEVEL, please reach out to your local retailer or the manufacturer for assistance. Ensure you have the product details ready for a more efficient inquiry.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities. Enjoy using your TOP RING BUBBLE LEVEL!

About Us

Brownells Norge

Brownells Norge - Komplett utvalg av ladeutstyr, våpendeler, kuler, hylser, kikkerter, optikk og luftvåpen

Heiveien 882
4985 Vegårshei

www.brownells.no