

77/22® BEAD FRONT SIGHT - BEAD FRONT SIGHT .464" FOR RUGER 77/22 BRASS

[Rifle Parts](#) > [Sights](#) > [Front Sights](#)

FITS: 77/22 R, RS, .22 LR; K77/22 RP, RSP, .22 LR; 77/44 RS, .44 Mag; M-96, .22 Mag



Attributes

- Name: [BEAD FRONT SIGHT .464" FOR RUGER 77/22 BRASS](#)
- Manufacturer: [RUGER](#)
- Product no.: 780000312
- Mfr. No.:
- Color: Gold
- Height: .464
- Make: Ruger
- Material: Brass
- Model: 77/22,77/44,M-96
- Style: Bead
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [RUGER 77/22® Bead Front Sight Safety Instruction Guide](#)
- [About Us](#)

RUGER 77/22® Bead Front Sight Safety Instruction Guide

Introduction

Thank you for choosing the RUGER 77/22® Bead Front Sight. This guide provides essential safety instructions and guidelines to ensure the safe use and installation of your product. Please read this guide carefully before using the product.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Keep the product out of the reach of children and vulnerable individuals.
- Regularly inspect the product for any signs of wear or damage before use.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay updated on product recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always handle firearms with care and follow all manufacturer safety guidelines.
- Ensure that the firearm is unloaded before installing or adjusting the front sight.
- Use only compatible models as specified: 77/22 R, RS, .22 LR; K77/22 RP, RSP, .22 LR; 77/44 RS, .44 Mag; M96, .22 Mag.
- Avoid using the product in adverse weather conditions that may affect visibility or handling.
- Do not attempt to modify the product in any way, as this may compromise safety.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Remove the old front sight if necessary, following the manufacturer's instructions.
- Align the RUGER 77/22® Bead Front Sight with the sight base on the firearm.
- Securely fasten the front sight using the appropriate tools, ensuring it is firmly in place.
- Check for proper alignment and stability before proceeding to use the firearm.

2. Usage:

- When aiming, ensure that your eye is aligned with the bead front sight for optimal accuracy.
- Practice safe shooting techniques at all times.
- Regularly clean and maintain the sight to ensure continued performance and safety.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- If the product is damaged or no longer usable, contact local authorities for proper disposal methods.

Contact Information for Further Support

For any inquiries or further assistance regarding the RUGER 77/22® Bead Front Sight, please refer to the manufacturer's contact information available in the product packaging or on the official website.

By following these guidelines, you will help ensure a safe and enjoyable experience with your RUGER 77/22®
Bead Front Sight. Thank you for your attention to safety.

About Us

Brownells Sverige

Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör

Brownells Sverige AB
Box 99
793 22 Leksand
Sverige

www.brownells.se