

SIGHT, FRONT, .595" HIGH

[Handgun Parts](#) > [Sights](#) > [Front Sights](#)

FITS: Bisley™ Large Frame; New Model Blackhawk®, .45; Super Blackhawk®, .44 Mag



Attributes

- Name: [SIGHT, FRONT, .595" HIGH](#)
- Manufacturer: [RUGER](#)
- Product no.: 780012047
- Mfr. No.: MR3645
- Color: Unfinished
- Height: .595
- Make: Ruger
- Model: Blackhawk
- Outline: None
- Style: Serrated
- Width: .125
- Delivery weight: 0.091kg
- Shipping width: 76mm
- Shipping length: 128mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for SIGHT, FRONT, .595" HIGH](#)
- [About Us](#)

Safety Instruction Guide for SIGHT, FRONT, .595" HIGH

Introduction

Thank you for choosing the SIGHT, FRONT, .595" HIGH, designed specifically for use with Bisley™ Large Frame and Ruger models such as the New Model Blackhawk® and Super Blackhawk®. This guide provides important safety instructions and usage information to ensure safe and effective use of your product.

General Safety Guidelines

- Always handle firearms and related accessories with care.
- Ensure that the sight is compatible with your specific firearm model before installation.
- Keep all firearms and accessories out of reach of children and unauthorized users.
- Regularly inspect the sight for damage or wear before use.
- If you experience any issues with the sight, discontinue use immediately and consult a professional.

Specific Safety Precautions for Use

- Use only with compatible models: Bisley™ Large Frame, New Model Blackhawk® (.45), and Super Blackhawk® (.44 Mag).
- Ensure that the firearm is unloaded before installing or adjusting the sight.
- Avoid using the sight in extreme weather conditions that may affect its performance.
- Do not modify the sight in any way, as this may compromise safety and functionality.
- Always wear appropriate eye protection when using firearms equipped with this sight.

Instructions for Installation and Usage

Installation Steps

1. **Ensure Safety:** Confirm that the firearm is unloaded and pointed in a safe direction.
2. **Remove Old Sight:** If applicable, carefully remove the existing sight from your firearm using appropriate tools.
3. **Align the New Sight:** Position the SIGHT, FRONT, .595" HIGH into the sight base, ensuring it is aligned correctly.
4. **Secure the Sight:** Tighten any screws or fasteners to secure the sight in place. Do not overtighten, as this may damage the sight or firearm.
5. **Check Alignment:** After installation, check the alignment of the sight with the barrel to ensure accuracy.

Usage Tips

- Familiarize yourself with the sight's features before using it in a live shooting environment.
- Practice aiming and shooting with the sight at a safe and controlled range.
- Regularly check the sight for tightness and alignment during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and firearm components.
- Do not dispose of the sight in regular household waste.
- Consider recycling options for metal and plastic components where available.

Contact Information for Further Support

For any questions or concerns regarding the SIGHT, FRONT, .595" HIGH, please refer to the manufacturer's website for support resources. Always ensure to have the product details on hand when seeking assistance.

Note: This guide is intended to provide essential safety information and should be kept for future reference. Always prioritize safety when handling firearms and related accessories.

About Us

Brownells Sverige

Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör

Brownells Sverige AB
Box 99
793 22 Leksand
Sverige

www.brownells.se