

# GRIP FRAME SCREW & PIVOT LOCK

[Handgun Parts](#) > [Grip Parts](#) > [Grip Screws](#)

FITS: Bisley™ - Common Parts; New Model Blackhawk®; New Model Single-Six®; Super Blackhawk®, .44 Mag; Super Blackhawk® Hunter, .44 Mag; Vaquero®



## Attributes

- Name: [GRIP FRAME SCREW & PIVOT LOCK](#)
- Manufacturer: [RUGER](#)
- Product no.: 780012082
- Mfr. No.:
- Make: Ruger
- Model: Blackhawk
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

## Item details

Made in USA

# Table of Contents

- Startpage
- GRIP FRAME SCREW & PIVOT LOCK Safety Instructions
- About Us

# GRIP FRAME SCREW & PIVOT LOCK Safety Instructions

## Introduction

Thank you for choosing the GRIP FRAME SCREW & PIVOT LOCK. This product is designed for use with various Ruger models, including the Bisley™, Blackhawk®, SingleSix®, Super Blackhawk®, and Vaquero®. Please read this safety instruction guide carefully to ensure safe and proper use of the product.

## General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Always follow the manufacturer's instructions for installation and usage.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly check for any product recalls or safety updates through the EU Safety Gate platform.
- Report any unsafe conditions or incidents involving this product to the relevant authorities.

## Specific Safety Precautions for Use

- Handle the GRIP FRAME SCREW & PIVOT LOCK with care to avoid injury.
- Ensure that the firearm is unloaded before installation or maintenance.
- Use appropriate tools when installing or adjusting the grip frame screw to avoid slipping or damaging the product.
- Do not modify the GRIP FRAME SCREW & PIVOT LOCK in any way.
- If you experience any issues with the product, cease use immediately and consult a qualified professional.

## Instructions for Installation and Usage

### 1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools, such as a screwdriver, for installation.

### 2. Installation Steps:

- Locate the grip frame on your Ruger model.
- Align the GRIP FRAME SCREW & PIVOT LOCK with the designated holes on the grip frame.
- Insert the screw and tighten it securely, but do not overtighten to avoid damage.

### 3. Usage:

- After installation, check that the grip frame is secure and stable.
- Regularly inspect the grip frame screw for any signs of wear or loosening.
- If the screw becomes loose during use, stop using the firearm and retighten the screw before continuing.

## Disposal Instructions

- Dispose of the GRIP FRAME SCREW & PIVOT LOCK in accordance with local regulations.
- Do not dispose of the product in regular household waste if it is damaged or no longer usable.
- Consider recycling options available in your area.

## Contact Information for Further Support

For safety inquiries or further support regarding the GRIP FRAME SCREW & PIVOT LOCK, please refer to the manufacturer's guidelines or your local regulations. Always ensure that you are in compliance with EU safety standards.

Thank you for prioritizing safety and for using the GRIP FRAME SCREW & PIVOT LOCK responsibly.

# About Us

## Brownells Sverige

**Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör**

Brownells Sverige AB  
Box 99  
793 22 Leksand  
Sverige

[www.brownells.se](http://www.brownells.se)