

CYLINDER LATCH SPRING PLUNGER, SS

[Handgun Parts](#) > [Action Parts](#) > [Cylinder Parts](#) > [Cylinder Plungers](#)

FITS: Bisley™ Large Frame; Bisley™ Small Frame; New Model Blackhawk®; New Model Single-Six®; Super Blackhawk®, .44 Mag; Super Blackhawk® Hunter, .44 Mag; Vaquero®



Attributes

- Name: [CYLINDER LATCH SPRING PLUNGER, SS](#)
- Manufacturer: [RUGER](#)
- Product no.: 780012111
- Mfr. No.: KXR07700
- Make: Ruger
- Model: Blackhawk
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for CYLINDER LATCH SPRING PLUNGER, SS](#)
- [About Us](#)

Safety Instruction Guide for CYLINDER LATCH SPRING PLUNGER, SS

Introduction

Thank you for purchasing the CYLINDER LATCH SPRING PLUNGER, SS. This product is designed to enhance the functionality of your firearm, specifically compatible with various Ruger models. It is essential to follow the safety guidelines outlined in this document to ensure safe and effective use.

General Safety Guidelines

- Always handle firearms with care and treat them as if they are loaded.
- Ensure that you are in a safe environment when using or installing this product.
- Keep this product out of reach of children and unauthorized users.
- Regularly inspect the product for signs of wear or damage before use.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before installing or replacing the latch spring plunger.
- Do not attempt to modify or alter the spring plunger in any way.
- Use appropriate protective gear, such as safety glasses, when handling firearms.
- Follow all manufacturer instructions and guidelines for the specific firearm model.
- Be aware of your surroundings and ensure that no one is in the line of fire when using the firearm.

Instructions for Installation and Usage

1. Preparation

- Ensure that your firearm is unloaded and pointed in a safe direction.
- Gather necessary tools for installation, including a screwdriver and safety glasses.

2. Installation Steps

- Remove the existing latch spring plunger from the firearm.
- Align the new CYLINDER LATCH SPRING PLUNGER, SS with the designated slot.
- Carefully insert the plunger, ensuring it is seated properly.
- Test the functionality of the plunger by operating the latch mechanism several times.
- Ensure that the plunger moves freely and does not obstruct any other components.

3. Usage

- After installation, verify that the firearm operates correctly with the new plunger.
- Regularly check the plunger for wear and replace it as necessary to maintain safety and functionality.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not throw the product in regular household waste.
- If the product is damaged or worn out, take it to a designated recycling facility or contact local waste management for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the CYLINDER LATCH SPRING PLUNGER, SS, please refer to the manufacturer's website or consult with a qualified firearms expert. Ensure that you have the product model and any relevant information ready for assistance.

By following these guidelines, you can ensure the safe and effective use of your CYLINDER LATCH SPRING PLUNGER, SS. Thank you for prioritizing safety and compliance with the EU General Product Safety Regulation.

About Us

Brownells Sverige

Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör

Brownells Sverige AB
Box 99
793 22 Leksand
Sverige

www.brownells.se