

# SIGHT SCREW, FRONT FOR RUGER MK I, MK II & SINGLE SIX

[Handgun Parts](#) > [Sights](#) > [Sight Parts](#) > [Sight Screws](#)

FITS: Mark I & II™ - Common Parts, .22; Old Model Single-Six®, .22



## Attributes

- Name: [SIGHT SCREW, FRONT FOR RUGER MK I, MK II & SINGLE SIX](#)
- Manufacturer: [RUGER](#)
- Product no.: 780022007
- Mfr. No.:
- Make: Ruger
- Model: Mark I, Mark II, Single Six
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

## Item details

Made in USA

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for SIGHT SCREW, FRONT SIGHT SCREW, FRONT FOR RUGER MK I, MK II & SINGLE SIX](#)
- [About Us](#)

# Safety Instruction Guide for SIGHT SCREW, FRONT SIGHT SCREW, FRONT FOR RUGER MK I, MK II & SINGLE SIX

## Introduction

Thank you for choosing the SIGHT SCREW, FRONT SIGHT SCREW, FRONT for your Ruger Mark I, Mark II, or Single Six. This guide provides essential safety instructions, installation tips, and proper usage guidelines to ensure a safe and effective experience with your product. Please read this document carefully before proceeding.

## General Safety Guidelines

- Ensure that you are using the product for its intended purpose only.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the sight screw for any signs of wear or damage before use.
- If you notice any defects or issues with the product, discontinue use immediately and seek assistance.
- Always follow local laws and regulations regarding firearm accessories and modifications.
- Report any unsafe products or accidents to the appropriate authorities.

## Specific Safety Precautions for Use

- Use appropriate tools when installing or adjusting the sight screw to prevent injury.
- Avoid forcing the screw into place; if resistance is encountered, check for misalignment.
- Wear safety glasses to protect your eyes from debris during installation.
- Handle all firearm components with care, ensuring they are unloaded before making any adjustments.
- Be aware of your surroundings and ensure a safe environment when handling firearms.

## Instructions for Installation and Usage

### 1. Preparation

- Ensure that your firearm is completely unloaded and safe to handle.
- Gather necessary tools: a screwdriver that fits the sight screw properly.

### 2. Installation Steps

- Locate the existing sight screw on your Ruger Mark I, Mark II, or Single Six.
- Remove the old sight screw carefully, taking care not to damage the surrounding components.
- Align the new sight screw with the mounting hole.
- Gently insert the sight screw and tighten it using the screwdriver. Do not overtighten, as this may strip the threads.

### 3. Usage

- After installation, check the alignment of the sight to ensure proper functionality.
- Test the sight screw by aiming at a target and making any necessary adjustments.
- Regularly check the tightness of the sight screw during routine maintenance.

## Disposal Instructions

- Dispose of any old or damaged sight screws in accordance with local waste disposal regulations.
- Do not throw the product in regular household waste; consider recycling options where available.

## **Contact Information for Further Support**

For any questions or concerns regarding the SIGHT SCREW, FRONT SIGHT SCREW, FRONT, please refer to your retailer or manufacturer's customer service for assistance.

Thank you for prioritizing safety and compliance while using your Ruger sight screw. Enjoy your shooting experience responsibly!

# About Us

## Brownells Sverige

**Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör**

Brownells Sverige AB  
Box 99  
793 22 Leksand  
Sverige

[www.brownells.se](http://www.brownells.se)