

GRIP FRAME SCREW, A-FRONT, SS

[Handgun Parts](#) > [Grip Parts](#) > [Grip Screws](#)

FITS: Bisley™ Large Frame; Bisley™ Small Frame; New Model Blackhawk®; New Model Single-Six™; Old Army™, .45; Super Blackhawk®, .44 Mag; Super Blackhawk ®Hunter, .44 Mag; Vaquero™



Attributes

- Name: [GRIP FRAME SCREW, A-FRONT, SS](#)
- Manufacturer: [RUGER](#)
- Product no.: 780022009
- Mfr. No.:
- Make: Ruger
- Model: Blackhawk
- Delivery weight: 0.005kg
- Shipping width: 83mm
- Shipping length: 146mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [GRIP FRAME SCREW, AFRONT, SS Safety Instruction Guide](#)
- [About Us](#)

GRIP FRAME SCREW, AFRONT, SS Safety Instruction Guide

Introduction

Thank you for choosing the GRIP FRAME SCREW, AFRONT, SS. This product is designed for use with specific firearm models, ensuring enhanced performance and reliability. It is essential to follow safety guidelines to ensure a safe and effective experience.

General Safety Guidelines

- Always handle firearms with care and in accordance with local laws and regulations.
- Ensure the product is compatible with your firearm model before use.
- Regularly inspect the GRIP FRAME SCREW for signs of wear or damage.
- Store the product in a safe place, away from children and unauthorized users.
- If you notice any defects or issues, discontinue use immediately and consult a qualified professional.

Specific Safety Precautions for Use

- Only use the GRIP FRAME SCREW with the following models: Bisley™ Large Frame Bisley™ Small Frame New Model Blackhawk® New Model SingleSix™ Old Army™, .45 Super Blackhawk®, .44 Mag Super Blackhawk® Hunter, .44 Mag Vaquero™
- Ensure that the firearm is unloaded before installation or maintenance.
- Avoid using excessive force when installing or removing the screw to prevent damage.
- Always wear safety glasses when working with firearms to protect your eyes from debris.
- Keep hands and tools clear of moving parts during installation.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is completely unloaded.
- Gather necessary tools, including a screwdriver compatible with the GRIP FRAME SCREW.

2. Installation

- Locate the grip frame area of your firearm.
- Align the GRIP FRAME SCREW with the designated hole in the grip frame.
- Gently insert the screw and handtighten it to ensure proper alignment.
- Use the screwdriver to securely tighten the screw without overtightening.
- Verify that the grip is firmly attached and does not wobble.

3. PostInstallation Check

- Inspect the installation to ensure there are no gaps or misalignments.
- Test the grip by holding the firearm to ensure it feels secure and stable.

4. Maintenance

- Regularly check the GRIP FRAME SCREW for tightness and signs of wear.
- If necessary, repeat the installation process to ensure secure fitting.

Disposal Instructions

- Dispose of the GRIP FRAME SCREW responsibly in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling options where available.

Contact Information for Further Support

For any inquiries regarding safety, installation, or product compatibility, please refer to the manufacturer's website or contact the designated support service. Always ensure to have the product details on hand for efficient assistance.

By following these guidelines and instructions, you can ensure a safe and enjoyable experience with the GRIP FRAME SCREW, AFRONT, SS. Thank you for your attention to safety and compliance with the EU General Product Safety Regulation.

About Us

Brownells Sverige

Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör

Brownells Sverige AB
Box 99
793 22 Leksand
Sverige

www.brownells.se