

# RUGER® M77® BEAD FRONT SIGHT HIGH - BEAD FRONT SIGHT HIGH .328" FOR RUGER M77 MARK II BRASS

[Rifle Parts](#) > [Sights](#) > [Front Sights](#)

FITS: M77® Bolt Action; M77® MK II Standard, .375, .416; M-77® MK II All-Weather®, Sporter; No. 1 - Common Parts Brass bead sight with detent hole in the rear.



## Attributes

- Name: [BEAD FRONT SIGHT HIGH .328" FOR RUGER M77 MARK II BRASS](#)
- Manufacturer: [RUGER](#)
- Product no.: 780077017
- Mfr. No.:
- Color: Gold
- Height: .406
- Make: Ruger
- Material: Brass
- Model: M77,M77 Mark II,No. 1
- Style: Blade
- Delivery weight: 0.005kg
- Shipping height: 3mm
- Shipping width: 89mm
- Shipping length: 152mm
- UPC: MPF06700-328

## Item details

Made in USA

# Table of Contents

- [Startpage](#)
- [RUGER® M77® Bead Front Sight High Safety Instruction Guide](#)
- [About Us](#)

# RUGER® M77® Bead Front Sight High Safety Instruction Guide

## Introduction

Thank you for choosing the RUGER® M77® Bead Front Sight High. This guide provides essential safety information and instructions for the safe use and installation of your new front sight. Please read this guide carefully and keep it for future reference.

## General Safety Guidelines

- Ensure that the front sight is compatible with your specific firearm model before installation.
- Always handle firearms with care and in accordance with local laws and regulations.
- Do not use the front sight if it appears damaged or defective.
- Keep this product out of reach of children and unauthorized users.
- Always store your firearm in a secure location when not in use.

## Specific Safety Precautions for Use

- Only use the RUGER® M77® Bead Front Sight High with the specified models: M77® Bolt Action, M77® MK II Standard, .375, .416, M77® MK II AllWeather®, Sporter, and No. 1.
- Ensure that the firearm is unloaded before attempting to install or adjust the front sight.
- Follow all manufacturer instructions for your firearm when installing the front sight.
- Avoid making adjustments to the front sight while the firearm is loaded or in a potentially dangerous situation.
- Regularly inspect the front sight for signs of wear or damage, and replace it if necessary.

## Instructions for Installation and Usage

### 1. Preparation:

- Ensure that your workspace is clean and free of distractions.
- Gather all necessary tools for installation, including a screwdriver and any other required instruments.

### 2. Installation:

- Verify that the firearm is unloaded.
- Remove the existing front sight if applicable, following the manufacturer's instructions.
- Align the RUGER® M77® Bead Front Sight High with the mounting hole on the firearm.
- Secure the front sight in place using the appropriate screws or fasteners.
- Ensure that the sight is firmly attached and does not wobble.

### 3. Usage:

- Familiarize yourself with the operation of your firearm and how the front sight affects aiming.
- Practice safe handling and shooting techniques at all times.
- Regularly check the alignment and condition of the front sight during use.

## Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and metallic waste.
- Do not dispose of the product in regular household waste.

- If the product is damaged or no longer usable, ensure it is securely stored until proper disposal can be arranged.

## **Contact Information for Further Support**

For any inquiries regarding safety, usage, or installation, please contact the manufacturer or your local authorized dealer.

## **Conclusion**

By following these safety instructions and guidelines, you can ensure the safe and effective use of your RUGER® M77® Bead Front Sight High. Always prioritize safety and responsibility when handling firearms and related accessories. Thank you for your attention to these important safety measures.

# About Us

## Brownells Sverige

**Brownells Sverige - Världens största leverantör av Vapendelar, Vapensmide Verktyg & Skyttetillbehör**

Brownells Sverige AB  
Box 99  
793 22 Leksand  
Sverige

[www.brownells.se](http://www.brownells.se)